sales@exlightsourcing.com · WhatsApp +86 147 7624 7782
www.exlightsourcing.com



GAD506

Large Lifting Lighting Unit

Generator-powered tower with pneumatic lift to 4.5 m or 6 m and LED, halogen or metal-halide lamps.

> General industrial model, not Ex-certified. Do not use in classified hazardous areas.

Specifications

Ingress protection	IP65
Lamps	4 × 100 W / 4 × 200 W LED, 4 × 500 W / 4 × 1000 W halogen, or 2 × 400 W / 2 × 1000 W metal halide
Luminous flux (LED)	4 × 12,000 lm or 4 × 24,000 lm
Generator	2000 W or 5000 W, AC 220 V / 50 Hz
Fuel tank	15 L or 25 L, about 13 h per fill
Lift	Pneumatic, 1.8 m to 4.5 m or 6 m, 30 ± 10 s
Control	Manual + remote
Dimensions	1550 × 500 × 800 mm (2 kW), 1580 × 600 × 900 mm (5 kW)
Weight	Lamp head 8 kg, mast 8 kg, 2 kW generator 40 kg

Features

- Lamp type and power configured to order
- Runs on mains for continuous use

Industries: Railway & Power Utilities, Fire & Emergency Rescue

OEM: Logo, housing colour, packaging and manual under your brand.