

HZ6133

Automatic Lifting Floodlight Tower

600W, 65,000 lm mains-powered tower with pneumatic lift to 4.5 m, voice prompts and battery backup.

> General industrial model, not Ex-certified. Do not use in classified hazardous areas.

Specifications

Ingress protection	IP65
Input	AC 220 V (mains or generator)
Backup battery	DC 14.4 V, 10 Ah, 1 h
Rated power	600W, 3 × 44 LEDs
Luminous flux	≥65,000 lm
Centre illuminance at 10 m	≥1300 lx
Colour temperature	6000 ± 500 K
Lift	4-section pneumatic, up ≤35 s, down ≤35 s
Head adjustment	0–90° horizontal, 0–120° vertical
Speaker	30W, MP3, ≥130 dB at 10 cm
Remote range	≥50 m
Operating temperature	-20 to 40 °C
Dimensions	390 × 643 × 1450 mm stowed, up to 4800 mm raised
Weight	70 ± 1 kg

Features

- Raises to 4.5 m in 35 seconds
- Three independently aimed heads
- Built-in battery keeps it lit through a power cut

- 10-inch wheels for one-person moves

Industries: Railway & Power Utilities, Fire & Emergency Rescue

OEM: Logo, housing colour, packaging and manual under your brand.